



HAILO 1-2-3 500 COMBI

The multipurpose aluminium scaffold with ingenious "Speed Lock" one-handed quick lock. Maximum working height of approx. 4.35 m.

THE KEY FEATURES

- Easy to handle and fitted with one-handed "Speed Lock" for lightweight, fast assembly
- Working platform with access hatch (61 x 46 cm)
- 2 crosspieces incl. 2 transport castors
- Step adjustment option



OTHER PRODUCT ADVANTAGES

- Scaffold and ladder in one
- Multipurpose: for use as a lean-to ladder and double ladder, as a small scaffolding unit for indoors and outdoors or as a platform for working
- 2 ladder sections of 12 rungs (27 x 27 mm) with safety joints for locking/releasing the ladder sections
- Platform dimensions: 136 x 50 cm
- 4 guard rails and 4 aluminium diagonal struts
- Upright dimensions: 60 x 22 mm
- Rung spacing: 260 mm
- Maximum load capacity 150 kg





PROPERTIES

- Rungs: 2x12
- Working height:
 - as scaffolding max. 435 cm,
 - as trestle ladder max. 285 cm,
 - as lean-to ladder max. 420 cm
- Weight: approx. 30.7 kg





SPECIFICATIONS

Level of equipment		3
Can be used in a free-standing position		✓
Working platform		✓
Step adjustment		✓
Ladder sections can also be used on their own		✓
Movable		✓
Dimensions of packaging (HxWxD)		A = 166 cm, B = 60 cm, C = 34 cm
Platform height		233 cm
Max. working height		435 cm
Weight		30,7 kg